



No alternate pump location available.



*Not available without Fast-Fill Waterfall Spout.



Rough-In Plumbing Measurements



SPECIFICATIONS:

GENERAL SPECIFICATIONS:

Tub Size	66" x 66" x 29" 168 cm x 168 cm x 74 cm
Bathing Well	40" long 22 1/2" wide 23 1/4" interior depth
Shipping Weight	569 lbs. / 258 kg
Tub Only Weight	247 lbs. / 112 kg
Tub Weight Filled	997 lbs. / 452 kg
Gallons to Overflow	95 gal. / 360 L
Gallons to Operate	1 bather: 76 gal. / 288 L 2 bathers: 57 gal. / 216 L

ELECTRICAL SPECIFICATIONS:

Pump	2 HP; 12 AMP; 110V
Inline Heater	1.5 kW; 12.5 AMP; 110V
Requirement	1-15 AMP 2 pole, separate circuit required protected with Class A GFCI
Blower	1 HP; 10.5 AMP; 110V
Requirement	1-15 AMP 1 pole, separate circuit required protected with Class A GFCI

This whirlpool will need to be hard wired to the breaker box. Three outlets will be supplied on the whirlpool.

This unit is not recommended for shower installations.

This unit has a 3/4" female waterfall fill spout connection.

STANDARD EQUIPMENT:

17 Hydrotherapy Jets including:

- 12 Shiatsu Back Jets
- 2 Full Size Pressure-Flo Hydrotherapy Jets
- 1 Recessed Rotary Massage Jet
- 2 Recessed Rotary Massage Elite Jets

Air Bath System:

- 1 HP Variable Speed Air Blower with 20-Minute Timer
- Electronic Control Panel
- Automatic Purge and Dry Cycle
- 600 Watt Air Heating System

Aquatic Quality Features:

- 2 HP Run-Dry Pump
- 1.5 kW Inline Maintenance Heater
- "Quiet Pad" Anti-Vibration Pump Mount for Quiet Pump Operation
- Shiatsu Electronic Control Panel with Preprogrammed Jet Sequencer
- Bath-Side Electronic Control Panel with Temperature Display
- Pulsating Neck Jet Pillow
- Integrally Molded Fast-Fill Waterfall Spout (valves not included)
- Chromatherapy
- 2 Extra Deep & Wide Contoured Lounge Seats and 4 Arm Rests
- Slip Resistant Floor
- Adjusta-Level Base
- Heat-bent Rigid PVC Piping for Optimum Sanitary Conditions
- Durable, Easy to Clean, Lucite® Cast Acrylic Surface
- Available in 8 Standard No-Charge Colors

UL & IAPMO Listed, Factory Tested Limited Lifetime Warranty

OPTIONAL EQUIPMENT:

- Comfort Pillow -- Oval or Rectangle
- Jet Finish
 - Chrome, Polished Brass, Gold, Polished Nickel or Satin Nickel
- Lift & Turn Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel or Oil Rubbed Bronze
- Cable Drive Waste and Overflow
 - Chrome, Polished Brass, Gold, Polished Nickel, Satin Nickel, Oil Rubbed Bronze or Color Matched (Bone, White and Biscuit Only)
- Hand Held Jet - Chrome or Polished Brass
- Factory Installed Rigid ABS Tile Flange
- Premium Colors

All acrylic colors featured by Aquatic match the industry's leading fixture manufacturers.

Fax-On-Demand Document # 1180



The manufacturer accepts a 1/4" variance. There are variations on each tub and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building should be measured from the tub; Aquatic Industries, Inc. assumes no responsibility for preparatory work. www.aquaticwhirlpools.com 800.555.5324